Preliminary_study_of_simple_me thods_to_get_the_average_spee d.pdf

Submission date: 10-Sep-2020 06:54PM (UTC+0700) Submission ID: 1383574587 File name: Preliminary_study_of_simple_methods_to_get_the_average_speed.pdf (402.45K) Word count: 1836 Character count: 9270

Preliminary study of simple methods to get the average speed using a smartphone's light sensor

Ea Cahya Septia Mahen^{1,*}, Seni Susanti¹, Bebeh Wahid Nuryadin², and Ade Yeti Nuryantini¹

¹UIN 7 nan Gunung Djati Bandung, Physics Education Departement, Bandung, Indonesia

²UIN Sunan Gunung Djati Bandung, Physics Departement, Bandung, Indonesia

Abstract. This paper reports on the result of a preliminary study of utilization of a smartphone ambient light sensor for get the average speeds of motion along a straight line based on experiments. We attach a smartphone to a dynamics train that travels across multiple light sources where the distance is already set. The main source of this experiment is obtained from the luminosity curve obtained from free android applications. From the curve, we can get position information against time. So from the data we can get the value of average speed. Then the use of the smartphone light sensor in physics experiments can be done easily and fun.

1 Introduction

Mobile devices such as smartphones and tablets are part of the daily life of many young people in recent years, and in many cases even for kids [1]. B sides its main functions to perform communications, the smartphone is c s pped with advanced features and functionality such as built-in camera, audio/video playback and recording, play games, play video, display photos, send/ receive email, social media, wireless into net, navigation, and much more [2]. smartphone is also equipped with several sensors, such as accelerometer, gyroscope, magnetometer, proximity sensor, ligs sensor, and in several higher-end phones includes barometer, thermometer, air humidity sensor, pedometer, and other as shown in Figure 1.




Fig. 1. Some sensors are embedded in the smartphone.

Recently, there are many published works explaining physics experiments that can be performed using sensor of smartphones. Smartphone pressure sensors can be used to measure vertical velocities [3], and analysing Stevin's

Corresponding author: ea.cahya@uinsgd,.ac.id

law [4]. Accelerometer and Gyroscope can be used to analyzing simple pendulum [5], study of two-dimensional oscillations [6], analysing free fall [7], introduction to the gncepts of acceleration and deceleration [8], Investigation of the rolling motion of a hollow cylinder [9], Investigation of kinetic friction [10], analyse free and damped oscillations [11] and coupled 12 cillations [12]. Magnetometer can be used measure the magnetic field of small magnets[13], and magnetic field due to electrical current in straight and loop wires[14].

Sans et al [15] demoralized the use of the smartphone light sensor to analyse a system of coupled oscillators. While Kapucu [16] utilizes light sensors to obtain average speeds by combining the physics knowledge of optics and kinematics. In this paper, we will present a preliminary study of a simpler method of obtaining average grade grades using light sensors without having to understand more deeply about optical concepts.

2 Experimental Method



Fig. 2. Set-up experiment

The Authors, published by EDP Sciences. This is an open access article distributed under the terms of the Creative Commons Attribution License 4.0 (http://creativecommons.org/licenses/by/4.0/).

Figure 2 shows the composition of the equipment used in the study. Equipment used include: smartphone (Vivo), trolley or motor dynamics train, rail, LED strip rails, solifies and double tip. In the experiments, the application of the light meter (Light meter on the physics tool Box) as shown in Figure 3 is preinstalled. Smartphones are affixed to the dynamics trains using double-sided tape with light sensor in a position facing the light source. Furthermore, the dynamics train is moved through a light source derived from the LED strip whose distance between the LEDs is made fixed 10 cm.

As the dynamics train moves past the LED arrangement, it captures the light intensity every time. Some peaks of illuminance when the light sensor on the smartphone right past the LED will be clamped on the physics toolbox ligh meter application. Since the distance between the previous LEDs is predetermined, then we can get the data of train trains dynamics through the light source. From this information we can determine to make the displacement curve over time so that the average speed can be determined.



Fig. 3. Light meter display on physics tool box.

4 Result and Discussion

In this preliminary study we obtained light intensity data recorded using the software lighmeter physiscs toolbox as shown in Figure 4. In the Figure we can see some peaks of light intensity. The peak of light intensity is obtained when the smartphone's light sensor is right in front of the light source. This is 3 sed on the illuminance Ev and luminous intensity Iv for a point light source $Ev = Iv/d^2$ [17]. The vals of illuminance (Ev) is inversely proportional to the distance d of the squared distant 3 So, the greatest value must be when the positioning of the smartphone's light sensor is right in front of the light source which is the closest one. The peak illuminance of

each lamp is not the same because the light intensity (iv) of each source is different.




Fig. 4. Curve of light intensity of smartphone.

From Figure 4 we know the time range that a smartphone passes through one light source to another. The time range traversed is relatively close to the average value of 0.71 s. From the information shown in Figure 2 we can create the vs. time displacement curve because the previous distance between the light sources is already set 10 cm.




Fig. 5. Curve of displacement versus time.

Figure 5 shows the displacement curve. The lines indicated by the curve form almost straight lines. Using linear fittings, we find the equation xf = xi + vt. The value of the slope of the displacement curve is the average speed [18-20]. From the graph we get the average speed is 14.198 \pm 0.0601 cm / s. To confirm this, we also compare the average speed 4 ore every 10 cm distance traveled by smartphone using ratio of the displacement Δx that occurs during a particular time interval Δt to that interval [18]: $v_{avg} = \Delta x / \Delta t = (x_f - x_i)/(t_f - t_{i)}$.

MATEC Web of Conferences 197, 02003 (2018) AASEC 2018

| No | t (s) | x (cm) | $\Delta t(s)$ | Δx (cm) | V _{average} (cm/s) |
|----|-------|-----------|---------------|--------------------|--------------------------------|
| 1 | 2,673 | 0 | | | |
| 2 | 3,398 | 10 | 0,725 | 10 | 13,793 |
| 3 | 4,111 | 20 | 0,713 | 10 | 14,025 |
| 4 | 4,843 | 30 | 0,732 | 10 | 13,661 |
| 5 | 5,556 | 40 | 0,713 | 10 | 14,025 |
| 6 | 6,232 | 50 | 0,676 | 10 | 14,793 |
| 7 | 6,92 | 60 | 0,688 | 10 | 14,535 |
| 8 | 7,612 | 70 | 0,692 | 10 | 14,451 |
| 9 | 8,324 | 80 | 0,712 | 10 | 14,045 |

Table 1. Value of average speeds.

The average speeds of every 10 cm shown in Table 1 is likely to be close to and close to the value of 14.198 cm obtained from the linear fitting value of the displacement curve. From the table, it is seen that the average speed has slightly changed up and down. This can be caused by several things such as obstacles in the rail path through which causing the movement of the train dynamics slightly inhibited.

5 Conclusion

We have successfully learned about the other benefits of the smartphone light sensor for use in experiments to determine the average speed. The experimental results show the light sensor can capture time data driven smartphone along the train dynamics through the light source. From these data, we can get information on data displacement versus time. From the data can be determined the average speed rating. So that the smartphone light sensor with the appropriate application can be used as a cheap and easy to use equipment to get the average moving average value of the object.

This work was supported by a research grant from UIN Sunan Gunung Djati Bandung, the Ministry of Religious Affairs, Republic of Indonesia

References

- 1. M. Kleinemeier, *Smartphones in Science Teaching* (*iStage2*). Berlin: Science on Stage Deutschland e.V., (2014).
- M. Sarwar and T. R. Soomro, "Impact of Smartphone's on Soci ety," *Eur. J. Sci. Res.*, vol. 98, no. 2, pp. 216–226, (2013).
- M. Monteiro and A. C. Marti, "Using smartphone pressure sensors to measure vertical velocities of elevators, stairways, and drones," *Phys. Educ.*, vol. 52, pp. 1–11, (2017).
- S. Macchia, "Analyzing Stevin's law with the smartphone barometer," *Phys. Teach.*, vol. 54, p. 373, (2016).
- P. Vogt and J. Kuhn, "Analyzing simple pendulum phenomena with a smartphone acceleration sensor,"

Phys. Teach., vol. 50, pp. 439-440, (2012).

- L. Tuset-sanchis and J. C. Castro-palacio, "The study of two-dimensional oscillations using a smartphone acceleration sensor: example of Lissajous curves," *Phys. Educ.*, vol. 50, no. 5, pp. 580–586, (2015).
- P. Vogt and J. Kuhn, "Analyzing free fall with a smartphone acceleration sensor," *Phys. Teach.*, vol. 50, pp. 182–183, (2012).
- M. Oprea and C. Miron, "Mobile phones in the modern teaching of physics," *Rom. Reports Phys.*, vol. 66, no. 4, (2014).
- C. Puttharugsa, S. Khemmani, P. Utayarat, and W. Luangtip, "Investigation of the rolling motion of a hollow cylinder using a smartphone," *Eur. J. Phys.*, vol. 37, no. 5, pp. 1–10, (2016).
- C. Baldock and R. Johnson, "Investigation of kinetic friction using an iPhone," *Phys. Educ.*, vol. 51, pp. 1–6, (2016).
- J. Carlos Castro-Palacio, L. Velázquez-Abad, M. H. Giménez, and J. a. Monsoriu, "Using a mobile phone acceleration sensor in physics experiments on free and damped harmonic oscillations," *Am. J. Phys.*, vol. 81, no. 6, p. 472, (2013).
- J. C. Castro-Palacio, L. Velázquez-Abad, F. Giménez, and J. a Monsoriu, "A quantitative analysis of coupled oscillations using mobile accelerometer sensors," *Eur. J. Phys.*, vol. 34, no. 3, pp. 737–744, (2013).
- E. Arribas, I. Escobar, and C. P. Suarez, "Measurement of the magnetic fi eld of small magnets with a smartphone: a very economical laboratory practice for introductory physics courses," *Eur. J. Phys.*, vol. 36, no. 6, pp. 1–11, (2015).
- R. D. Septianto, D. Suhendra, and F. Iskandar, "Utilisation of the magnetic sensor in a smartphone for facile magnetostatics experiment : magnetic field due to electrical current in straight and loop wires," *Phys. Educ.*, vol. 52, pp. 1–7, (2017).
- J. A. Sans, F. J. Manjon, A. L. J. Pereira, Gomez-Tejedor J A, and J. Monsoriu, "Oscillations studied with the smartphone ambient light sensor," *Eur. J. Phys.*, vol. **1349**, pp. 1349–1354, (2013).
- S. Kapucu, "Finding the average speed of a lightemitting toy car with a smartphone light sensor," *Phys. Educ.*, vol. **52**, no. 4, p. 45001, Jul. (2017).
- A. E. Taylor, *Illumination Fundamentals*. New York: Lighting Research Center, Rensselaer Polytechnic Institute, Troy, (2000).
- Halliday and Resnick, Fundamental of Physics 10th Edition, vol. 1. (2015).
- 19. P. a. Tipler and G. Mosca, *Physics for Scientists and Engineers*. (2009).
- H. Young and R. Freedman, University physics with modern physics. (2007).

Preliminary_study_of_simple_methods_to_get_the_average_spe.

| ORIGIN | ALITY REPORT | | | | |
|--------|-----------------------------------------|----------------------------------------------------------------------|----------------------------|------------------|-------|
| SIMIL | | 9% INTERNET SOURCES | 11% PUBLICATIONS | 8% STUDENT PA | \PERS |
| PRIMA | RY SOURCES | | | | |
| 1 | Submitted Manageme Student Paper | to School of Bu ent ITB | isiness and | | 3% |
| 2 | hdl.handle | .net | | | 2% |
| 3 | a light-emi | pucu. "Finding tting toy car wit hysics Educatio | h a smartphon | | 1% |
| 4 | Submitted Student Paper | to Middle East | Technical Univ | versity | 1% |
| 5 | Submitted Singapore Student Paper | to Nanyang Te | chnological Ur | niversity, | 1% |
| 6 | Submitted Student Paper | to Taylor's Edu | cation Group | | 1% |
| 7 | Nuryantini, | Nuryadin, Fitri / , Irfana D. Fary [–] erry Iskandar. | uni, Mikrajuddi | n | 1% |

manganese-doped boron carbon oxynitride (BCNO) phosphor materials: facile approach and photoluminescence properties", RSC Advances, 2017

Publication

Publication

| 8 | www.semanticscholar.org | 1% |
|----|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----|
| 9 | A Çoban, M Erol. "Teaching and determination of kinetic friction coefficient using smartphones", Physics Education, 2019 Publication | 1% |
| 10 | euagenda.eu Internet Source | 1% |
| 11 | Moceheb Lazam Shuwandy, B. B. Zaidan, A. A. Zaidan, A. S. Albahri. "Sensor-Based mHealth Authentication for Real-Time Remote Healthcare Monitoring System: A Multilayer Systematic Review", Journal of Medical Systems, 2019 Publication | 1% |
| 12 | S D Fatmaryanti, Y Al Hakim, Ashari. "Comparative study of magnetic fields | <1% |

measurements with logger lite and Arduino on electronic devices", IOP Conference Series: Materials Science and Engineering, 2018

digitalcommons.tamusa.edu



| Exclude quotes | On | Exclude matches | Off |
|----------------------|----|-----------------|-----|
| Exclude bibliography | On | | |